



saldatrici

Saldatrice manuale da banco mod. PFS

- Larghezza filo di saldatura: 3 mm
- Tempo di saldatura regolabile tramite timer
- Disponibile anche con taglierino

Materiali utilizzati: PP – PE 300my - PET – pluribol – buste metallizzate – accoppiati.

Saldatrici a pedale mod. S-Type

- Larghezza filo di saldatura: 5 mm
- Tempi di saldatura e raffreddamento regolabili tramite timer
- Magnete di saldatura e taglierino di serie
- Supporto bobina e dispositivo di fermo bobina
- Piano di lavoro regolabile da 90° a 180°

Materiali utilizzati: Film foglia unica, tubolare e monopiega - PP – PE 300my - PET – pluribol – buste metallizzate – accoppiati.

Optionals: doppia barra saldante, macchina in acciaio inox e dispositivo datario.

Table top impulse sealers mod. PFS

- Sealing wire width: 3 mm
- Adjustable sealing time through a timer
- Available also with cutter

Employed material: PP – PE 300my – PET – pluribol - metal bags – combined materials.

Impulse sealer machines with pedal mod. S-Type

- Sealing wire width: 5 mm
- Adjustable sealing and cooling time through a timer
- Standard sealing magnet and cutter
- Roll support and grip roll device
- Adjustable table plate from 90° to 180°

Employed materials: single sheet, tubular and centre fold film – PP – PE 300my – PET – pluribol – metal bags – combined materials.

Optionals: double sealing bar, stainless steel machine and date stamping device.

CARATTERISTICHE TECNICHE / TECHNICAL DATA

MOD.		PFS200 PFS200C	PFS300 PFS300C	PFS400 PFS400C	PFS500 PFS500C	EXTRA LONG 600HI
Barra saldante Sealing bar	mm	200	300	400	500	600
Alimentazione elettrica Power supply	V	220	220	220	220	220
Potenza assorbita Absorbed power	W	300	400	600	600	800
Dimensioni macchina Machine dimensions	mm	80x320 x150 H.	85x450 x180 H.	80x550 x180 H.	85x630 x180 H.	130X800 x210 H.
Peso netto Net weight	Kg	2,9	4,2	5,2	5,8	10,8
MOD. S-TYPE		S320/5 *SD320/5	S420/5 *SD420/5	S620/5 *SD620/5	S820/5 *SD820/5	S1020/5 *SD1020/5
Barra saldante Sealing bar	mm	320	420	620	820	1020
Alimentazione elettrica Power supply	V	220	220	220	220	220
Potenza assorbita Absorbed power	W	500/750	450/650	350/500	850/1300	850/1300
Dimensioni macchina Machine dimensions	mm	520x650 x1100 H.	620x650 x1100 H.	820x650 x1100 H.	1020x650 x1100 H.	1220x650 x1100 H.
Peso netto Net weight	Kg	24	28	34	40	46

* SD: doppia barra saldante/double sealing bar

saldatrici



Saldatrici manuali da banco e saldatrici a pedale con magnete di saldatura, conformi alla normativa CE. Ideali per sigillare buste di vario materiale e spessore, disponibili anche con taglierino.

Table top hand impulse sealers and pedal impulse sealers with sealing magnet, CE rules. Ideal for sealing bags of several materials and thicknesses. Available also with cut.

